

# Spiralite® 195

## PVC Corrugated Heavy Duct Hose



### Appearance/Construction

Clear flexible PVC with white helix.  
Corrugated exterior, smooth interior.

### Benefits

Lightweight and highly flexible.

### General Applications

Air ducting.  
Light suction, vacuum.  
Also available in low-temperature version (194-00).

### Temperature Range

-10° F to +130° F

### Standard Lengths

1-1/2" thru 6" 100'  
7" and 8" 50'  
10" and 12" 25'

Nominal Size (inch)	Approx. O.D. (inch)	Rec. Max. W.P. @ 72° F (psi)	Vacuum Rating @ 72° F (in/HG)	Rec. Min. Bend Radius @ 72° F (inch)	Approx. B.P. @ 72° F (psi)	Approx. Weight (lbs./ft.)
1-1/4"	1.95	50	28	3	150	0.31
1-1/2"	1.83	40	28	3	120	0.32
2"	2.40	35	28	4	100	0.48
2-1/2"	2.91	25	26	5	75	0.60
3"	3.54	25	28	6	75	0.86
4"	4.56	25	28	8	75	1.29
5"	5.63	25	20	10	75	1.93
6"	6.82	25	20	12	75	3.04
7"	7.90	20	20	15	60	3.80
8"	8.91	20	16	18	60	4.32
10"	11.18	20	16	23	60	7.47
12"	13.15	20	16	29	60	8.87

# Spiralite® 310

## PVC Yellow 570 PSI Spray Hose



### Appearance/Construction

Yellow PVC ribbed exterior and tube.  
Spiral braid reinforcement.  
Made in Japan.

### Benefits

Excellent blend of flexibility, durability and value.

### General Applications

Agricultural spraying.  
Pest control.  
Compressed air and water.

### Temperature Range

-10° F to +130° F

### Standard Lengths

300'  
3/8" and 1/2" also available in 400'

Nominal Size (inch)	Inside Diameter (inch)	Approx. O.D. (inch)	Rec. Max. W.P. @ 72° F (psi)	Approx. B.P. @ 72° F (psi)	Approx. Weight (lbs./300 ft.)
1/4"	19/64	34/64	570	1,710	24
3/8"	25/64	43/64	570	1,710	35
1/2"	33/64	52/64	570	1,710	47
5/8"	40/64	62/64	570	1,710	64
3/4"	48/64	1-5/64	570	1,710	80